Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01

Date: April 5th 2022 Version: 2.0

Section 1: Identification of the substance or mixture and the company

1.1. Product Identifier

EM-Tec STC15 Methyl ethyl ketone (MEK) solvent / thinner / cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Diluting, removing and cleaning of EM-Tec AG15 silver paint

1.3. Details of the supplier of the Safety Data Sheet

Vof Micro to Nano Tappersweg 91 2031ET Haarlem Netherlands Tel: +31(0)85-2013155 E: info@microtonano.com

1.4 Emergency telephone number

112 (NLD) or your national emergency telephone number for chemical spills, leaks, fires, exposures or accidents

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Physical:	Flammable liquid, category 2
Health:	Eye irritation, category 2
	May cause drowsiness or dizziness
Environment:	Not classified
Other hazards:	Not classified

Classification according to Regulation EC Nr. 1272/2008

F: HIGHLY FLA	MMABLE
Xi: Irritant	
Health:	R36: Irritating to eyes
	R66: Repeated exposure may cause skin dryness or cracking
	R67: Vapours may cause drowsiness and dizziness
Physical	R11: Highly flammable



Micro to Nano

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155

E info@microtonano.com

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01

Environment: Other hazards:

Not classified Not classified

Regulation EC Nr. 1907/2006 Art.31

Date: April 5th 2022 Version: 2.0

2.2 Labeling elements

Labelling accordance to Regulation EC Nr. 1272/2008

	< <p><</p>
	\bigtriangledown \checkmark
Hazard pictogramm(s):	•
Signal word:	Danger
Hazard statement(s):	H225: Highly flammable liquid and vapour
	H319: Causes serious eye irritation
	H336: May cause drowsiness or dizziness
Precautionary statement(s	-
Prevention:	P102: Keep out of reach of children
	P210: Keep away from heat, hot surfaces, sparks, open flames and other
	ignition sources. No smoking
	P233: Keep container tightly closed
	P241: Use explosion proof electrical/ventilating/lighting/intrinsically safe
	equipment
	P242: Use only non-sparking tools
	P243: Take precautions against static discharge
	P261: Avoid breathing mist/vapours/spray
	P270: Do not eat, drink or smoke when using this product
	P 271: Use outdoors or in well ventilated area (fume hood) P280: Wear protective gloves/protective clothing/eye protection/face
	protection
Response:	P331: No NOT induce vomiting
Response.	P312: Call a poison center/doctor/physician/first aider if you feel unwell
	P370+378: In case of fire: Use dry chemical powder, alcohol-resistant foam or
	carbon dioxide (CO2) for extinction
P305+F	P351+P338: If in eyes: Rinse cautiously with water for several minutes. Remove
	contact lenses if easy to do. Continue rinsing.
ſ	P337+P313: If eye irritation persists: Get medical attention
	P361+P353: If on skin (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water/shower
I	P304+P340: If inhaled: Remove person to fresh air and keep comfortable for



Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155

E info@microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01 Date: April 5th 2022 Version: 2.0

	breathing
Storage: P	403+P235: Store in a well-ventilated place. Keep cool
	P405: Store locked up
Disposal:	P501: Dispose of contents/container in accordance with local regulations
Supplemental hazard info:	None

2.3 Other hazards

None

Section 3: Composition / information on components

3.1. Substances

1. CAS No 2. EC No 3. Index No 4. REACH No	% (weight)	Name	Classification according to directive 67/548/EEC [DSD]	Classification according to regulation Nr 1272/2008 [CLP]
78-93-3 201-159- 606-002-00-3 01-2119457290-43-xxxx	100	MEK Methyl ethyl ketone Synonym: Butan-2-on	R11R36R66R67	Flam. Liq. 2, Eye Irri. 2A, STOT SE 3; H225, H319, H336, EUH066

(* Explanation notes: see section 16)

3.2 Mixtures

Not applicable

Section 4: First aid measures

4.1. Description of first aid measures

Contact with eyes:	Rinse cautiously with water for several minutes. If possible, remove contact lenses. Continue rinsing. Seek medical attention if irritation persists.
Contact with skin:	Wash with water and soap. Seek medical attention if irritation persists.
Inhalation:	Fresh air, keep warm and at rest. Seek medical attention of ill effects occur
Ingestion:	If swallowed, do not induce vomiting Seek immediate medical advice

Micro to Nano

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155

E info@microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01 Date: April 5th 2022 Version: 2.0

If vomiting appears imminent or occurs hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. Never give liquid to a person with reduced awareness Give water to rinse out mouth, then provide water slowly as much as casually can comfortably drink Avoid giving milk or oils Avoid giving alcohol

4.2. Important symptoms and effects, either immediate or delayed

Inhalation:	Excessive inhalation of solvent vapours may give rise to nausea, blurred vision,
	fatigue, headaches and dizziness
Ingestion:	May cause respiratory and digestive tract irritation
	Symptoms: sore throat, abdominal pain, nausea, vomiting
Skin contact:	Continuous exposure: Dry skin. Cracking of skin
Eye contact:	Irritating to eyes
	Symptoms: redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment

General advice:	If you feel unwell, seek medical advice; show product label if possible
	If symptoms persist, always call a doctor

Section 5: Firefighting Measures

5.1. Extinguishing media

Alcohol resistant foam. Water spray. Polyvalent foam. BC powder. Carbon dioxide. Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Direct fire hazard. Highly flammable. Gas / vapour flammable with air within explosion limits. Indirect fire hazard. May be ignited by sparks. Gas / vapour spreads to floor level: ignition hazard. Direct explosion hazard Indirect explosion hazard Upon combustion CO and CO2 are formed. Violent to explosive reaction with many compounds. Keep away from strong oxidisers.

5.3 Advice to firefighters

Fight fire from a safe distance, with adequate cover Do not move the load if exposed to heat.



Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155E info@microtonano.comI www.microtonano.com

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01

> In case of fire; do not breathe fumes Wear self-contained breathing apparatus for fire fighting

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing including eye/face protection

6.2 Environmental precautions

Avoid release to the environment Do not allow to enter public sewers and waterways

6.3 Methods and material for containment and clean up

Absorb spillage in suitable inert material Clean up spills immediately Avoid breathing vapours Control personal contact with the substance, by using protective equipment Collect spillage, absorbed spillage and wipes in a flammable waste container Wash spill area with soap and water to remove last traces of residue

6.4 Reference to other sections

For further information see section 8

Section 7: Handling and storage

7.1. Precautions for safe handling

Keep away from sources of ignition Take precautions against static discharges Equipment should be grounded Use explosion proof electrical/ventilating/lighting/equipment Only use non-sparking tools Do not breathe aerosols or vapours Ensure adequate ventilation Avoid contact with skin and eyes

Micro to Nano

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155

- E info@microtonano.com
- I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Date: April 5th 2022 Version: 2.0



Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01 Regulation EC Nr. 1907/2006 Art.31

Date: April 5th 2022 Version: 2.0

Wash thoroughly after use Wear protective gloves/protective clothing/eye protection/face protection Have eyewash bottles available

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place Keep away from ignition sources Store away from oxidising agents Keep cool Keep out of reach of children

7.3 Specific end uses(s)

Solvent / thinner / cleaner for EM-Tec AG15 silver paint.

Section 8: Exposure control and personal protection

8.1. Control parameters

Exposure limits

Occupational exposure limits (OEL)

Ingredient	Material Name	Source	TWA	STEL	Peak	Notes
Methyl ethyl	MEK	UK	200 ppm	Not available	Not available	Not available
ketone		EU	200 ppm	300 ppm	Not available	Not available

8.2 Exposure controls

Control procedures:	Ensure adequate ventilation Keep away from heat sources and ignition sources Take precautions against static discharges
Personal protection:	Take precautions to avoid contact with eyes and skin when handling the products
	Ensure adequate ventilation
Inhalation:	In case of insufficient ventilation, wear suitable respiratory equipment:
	Air purifying respirator with organic gas/vapour cartridge (type A)
Hands and skin:	Wear suitable gloves against chemicals; recommended gloves: Nitrile
Eyes:	Wear safety goggles or full-face protection



Micro to Nano

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155 E info@microtonano.com

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01 Regulation EC Nr. 1907/2006 Art.31

Date: April 5th 2022 Version: 2.0

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance/physical state: Colour:	Liquid colourless
Odour:	Acetone like pungent aromatic / sweet / fruity odour
рН	7
Melting point:	-86°C
Boiling point/range:	82°C
Flash point:	-9°C (closed cup)
Relative evaporation rate:	>1
Explosion limits: upper limit:	11.5 %
lower limit:	1.8 %
Vapour pressure:	12.6 kPa
Relative density:	0.805 g/cm3 @ 20°C
Solubility in water:	soluble; 250 g/l
Auto-ignition:	515°C
Viscosity:	0.42 Pa.s

9.2 Other information

VOC:

100% MEK

Section 10: Stability and reactivity

10.1. Reactivity

Heating may cause fire.

10.2 Chemical stability

Stable under prescribed storage conditions

10.3 Possibility of hazardous reactions

Not known



Tappersweg 91 2031ET Haarlem The Netherlands

- E info@microtonano.com
- I www.microtonano.com

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner **Document Nr.:** SDS001150021700-01

10.4 Conditions to avoid

Avoid overheating, ignition sources and incompatible substances

10.5 Incompatible materials

Strong oxidising agents, strong bases, strong acids

10.6 Hazardous decomposition products

Fume, CO, CO2.

Section 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure:

Inhalation:Inhalation of solvent vapours may give rise to nausea, headaches and dizzinessSkin contact:Not classifiedEye contact:Irritation to eyes

Toxicological data:

Ingredient	Toxicity	Irritation
MEK Methyl ethyl ketone	Dermal (rabbit) LD50: 5000mg/kg	Eye - irritant
	Inhalation (rat) LC50: 20mg/L/4hrs	
	Oral (rat) LD50: 2000 mg/kg	Skin - mild

Section 12: Ecological information

12.1. Toxicity

Not classified

12.2 Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
MEK Methyl ethyl ketone	LOW	Medium



Micro to Nano

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands Regulation EC Nr. 1907/2006 Art.31

Date: April 5th 2022 Version: 2.0

> E info@microtonano.com I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01

Date: April 5th 2022 Version: 2.0

12.3 Bioaccumulative potential

Ingredient	Bioaccumulation
MEK Methyl ethyl ketone	Will not bio-accumulate

12.4 Mobility in soil

Ingredient	Mobility in soil
MEK Methyl ethyl ketone	нідн

12.5 Results of PBT and vPvB assessment

No information available

12.6 Hazardous decomposition products

No experimental data available

Section 13: Disposal considerations

13.1. Waste treatment methods

Product:

This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point. National regulations: Disposal should be in accordance with local, state or national legislation.

Section 14: Transport information

Labels required:





Tappersweg 91 2031ET Haarlem The Netherlands

- E info@microtonano.com
- I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01

Date: April 5th 2022 Version: 2.0

14.1. UN number		
UN-number:	1193	
14.2 UN proper shipping name		
Proper shipping name:	Ethyl Methyl Ketone (Methyl Ethyl Ketone)	
14.3 Transport hazard class(es)		
Class: ADR/RID-Classification code:	3 F1	
14.4 Packing group		
Packing: Limited Quantity	II 5L	
14.5 Incompatible materials		
ADR/RID- Environmentally hazardous IMDG-Marine pollutant: IATA/ICAO-Environmentally hazardou	No relevant data	
14.6 Special precautions for user		
ADR/RID-Tunnel code: IMDG-EMS:	(D/E) F-E, S-D	
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC code		
Not applicable		
Section 15: Regulatory information		
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
UN-number:	1193	

Micro to Nano

l-n

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155E info@microtonano.comI www.microtonano.com

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01

Regulation EC Nr. 1907/2006 Art.31

Date: April 5th 2022 Version: 2.0

15.2 Chemical safety assessment

No information available

Section 16: Other information

RoHS Directive Compliant

This product is fully compliant with the directive 2100/65/EU Annex II (RoHS). It does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's or PBDE's.

WEEE

This product is not a piece of electrical or electronic equipment, and it therefore not governed by Directive 2002/96/EC on waste electrical and electronic equipment (WEEE)

Abbreviations:

Asp. Tox	Aspiration hazard
Carc.	Carcinogenicity
Exp.	Exposure
Flam.	Flammable
GHS	Global Harmonised System of Classification of Labelling Chemicals
Irrit.	Irritant
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
N/A	Not applicable
N/E	Not estimated
PBT	Persistent Bioaccumulative and Toxic
WEL	Workplace Exposure Limit
Repr.	Reproductive toxicant
RoHS	Restriction of Hazardous Substance
SEM	Scanning Electron Microscope
STEL	Short-Term Exposure Limit
STOT	Specific Target Organ Toxicity
TCLo	Lowest published toxic concentration
vPvB	very Persistent and very Bioaccumulative
WEEE	Waste Electrical and Electronic Equipment

DSD / DPD label elements





Tappersweg 91 2031ET Haarlem The Netherlands

- E info@microtonano.com
- I www.microtonano.com

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01

Full Text Risk and Hazard codes

- H225 Highly flammable liquid and vapours
- H226 Flammable liquid and vapour.
- H228 Flammable solid
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness
- H340 May cause genetic defects.
- H351 Suspected of causing cancer.
- H360 May damage fertility or the unborn child.
- H370 Causes damages to organs.
- H371 May cause damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R20/22 Harmful by inhalation and if swallowed.
- R36 Irritating to eyes.
- R37 Irritating respiratory system.
- R38 Irritating to skin.
- R52 Harmful to aquatic organisms
- R63 Possible risk of harm to the unborn child.
- R65 Harmful May cause long damage if swallowed
- R66 Repeated exposure may cause skin dryness and cracking.
- R67 Vapours may cause drowsiness and dizziness

Safety advice:

- S02 Keep out of reach of children.
- S09 Keep container in a well-ventilated place.
- S13 Keep away from food, drinks, and animal feeding stuff.
- S16 Keep away from sources of ignition. No smoking.
- S23 Do not breath gas/fumes/vapour/spray.
- S26 In case of contact with eyes, rinse with plenty of water and seek medical help.

Micro to Nano

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands

T +31-85-2013155

- E info@microtonano.com
- I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Date: April 5th 2022 Version: 2.0



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC15 MEK solvent / thinner / cleaner Document Nr.: SDS001150021700-01

Date: April 5th 2022 Version: 2.0

- S28 After contact with skin, wash immediately with detergent and plenty of waterways.
- S29 Do not empty in drains.
- S33 Take precautionary measures against static discharges.
- S35 This material and its container must be disposed of in a safe way.
- S36 Wear suitable protective clothing.
- S37 Wear suitable gloves.
- S38 In case of insufficient ventilation, wear suitable respiratory equipment.
- S39 Wear eye / face protection.
- S40 In case of insufficient ventilation, wear suitable respiratory equipment.
- S41 In case of fire and/or explosion; DO NOT breathe fumes.
- S43 In case of fire use....
- S45 In case of accident or if you feel unwell, immediately contact Doctor or Poisons information center (show label if possible).
- S46 If swallowed, seek immediate medical advice and show label if possible.
- S52 Not recommended for interior use on large surfaces.
- S53 Avoid exposure obtain special instructions before use.
- S56 Dispose of this material and its container at hazardous or special waste collection point.
- S57 Use appropriate container to avoid environment contamination.
- S61 Avoid release to the environment
- S63 In case of accident by inhalation, remove casualty to fresh air and keep at rest.
- S64 If swallowed, rinse mouth with water (only if person is conscious)

This product should be stored, handled, and used in accordance with good industrial hygiene practices and in accordance with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe the product from the point of view of safety requirements. It does not guarantee any specific properties.

It is the responsibility of the user to query and verify any information seeming suspect or where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, state, federal and international regulations.



Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155 E info@microtonano.com