Regulation EC Nr. 1907/2006 Art.31

September 14th 2017

Document Nr.: SDS00115002431A-02 **Version:** 2.0

Section 1: Identification of the substance or mixture and the company

1.1. Product Identifier

EM-Tec AG31 fast cure, high conductivity silver filled epoxy

1.2 Relevant identified uses of the substance or mixture and uses advised against

Silver filled electrically conductive epoxy resin for use with hardener.

Making electrically conductive bonds. Uses advised against: Not available

1.3. Details of the supplier of the Safety Data Sheet

Vof Micro to Nano Wateringweg 79 2031EK Haarlem Netherlands

Tel: +31(0)85-2013155 E: info@microtonano.com

1.4 Emergency telephone number

112 (NLD) or your national emergency telephone number for chemical spills, leaks, fires, exposures or accidents

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Physical: Low flammability

Health: Skin corrosion/irritation category 2
Environment: Chronic aquatic hazard category 1

Acute aquatic hazard category 1

Other hazards: None

Classification according to Regulation EC Nr. 1272/2008

Xi: Irritant Xn: Harmful

Health: R38: Irritating to skin **Physical** Not classified

Environment: R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in



Wateringweg 79 T +31-85-2013155
2031EK Haarlem E info@microtonano.com
The Netherlands I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part A

Document Nr.: SDS00115002431A-02

Date: September 14th 2017

Version: 2.0

the aquatic environment

Other hazards: Not classified

2.2 Labeling elements

Labelling accordance to Regulation EC Nr. 1272/2008

Hazard pictogramm(s):







Signal word: Warning

Hazard statement(s): H317: May cause an allergic skin reaction H341: Suspected of causing genetic defects

H410: Very toxic to aquatic life with long lasting effects

Precautionary statement(s)

Prevention: P102: Keep out of reach of children

P201+P202: Obtain special instructions before use. Do not handle until safety

precautions have read and understood P261: Avoid breathing fumes/vapours/mist

P270: Do not eat, drink or smoke when using this product

P 272: Contaminated work clothing should not be allowed out of the

workplace

P 273: Avoid release to the environment

P280: Wear protective gloves/protective clothing/eye protection/face

protection

Response:

P308+P313: If exposed or concerned: Get medical attention P302+P352: If on skin: Wash with plenty of water and soap.

P333+P313: If skin irritation or a rash occurs: Get medical attention P362+P364: Take of contaminated clothing and wash before reuse

P391: Collect spillage

Storage: P405: Store locked up

Disposal: P501: Dispose of contents/container in accordance to local/regional/

international regulations

Supplemental hazard info: none

2.3 Other hazards

Argyria warning: Long term ingestion or inhalation of silver dust can lead to an irreversible

blue-grey discoloration of the skin

Defats skin: Prolonged and repeated exposure may cause skin dryness or cracking



Wateringweg 79 T +31-85-2013155
2031EK Haarlem E info@microtonano.com
The Netherlands I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS00115002431A-02 **Version:** 2.0

Section 3: Composition / information on components

3.1. Substances

Not applicable

3.2 Mixtures

Component	CAS Nr.	WT%
Silver flakes (<1mm) - Ag	7440-22-4	67
4,4'-methylene bis [N,N-bis(2-oxiranylmethyl) aniline]	28768-32-3	33

(* Explanation notes: see section 16)

Section 4: First aid measures

4.1. Description of first aid measures

Contact with eyes: Rinse cautiously with water for several minutes. If possible, remove contact

lenses. Continue rinsing.

Seek medical attention if irritation persists.

Contact with skin: Wash with water and soap.

Seek medical attention if irritation persists.

Inhalation: Fresh air, keep warm and at rest.

Seek medical attention of ill effects occur

Ingestion: If swallowed, do not induce vomiting

Seek immediate medical advice

If vomiting appears imminent or occurs hold patient's head down, lower than their

hips to help avoid possible aspiration of vomitus. Never give liquid to a person with reduced awareness

Give water to rinse out mouth, then provide water slowly as much as casually can

comfortably drink Avoid giving milk or oils Avoid giving alcohol

4.2. Important symptoms and effects, either immediate or delayed

Inhalation: May cause irritation of the respiratory tract

Symptoms: cough, sore throat, asthma



Wateringweg 79 2031EK Haarlem The Netherlands T +31-85-2013155

E info@microtonano.com
I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS00115002431A-02 **Version:** 2.0

Ingestion: May cause digestive tract irritation

Symptoms: sore throat, abdominal pain, nausea, vomiting

Skin contact: Mildly irritating to skin

Symptoms: redness and pain

Eye contact: Irritating to eyes

Symptoms: redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment

General advice: If you feel unwell, seek medical advice; show product label if possible

If symptoms persist, always call a doctor

Section 5: Firefighting Measures

5.1. Extinguishing media

Use dry sand, graphite powder or dry sodium chloride based extinguishers. DO NOT USE WATER, CO2 or FOAM

5.2 Special hazards arising from the substance or mixture

Not flammable or combustible, but will burn if involved in a fire. Produces carbon oxides (CO, CO2), irritating smoke and toxic fumes in fires

5.3 Advice to firefighters

Fight fire from a safe distance, with adequate cover Wear self-contained breathing apparatus and full firefighting turn-out gear

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear suitable protective clothing including eye/face protection

6.2 Environmental precautions

Avoid release to the environment Do not allow to enter public sewers and waterways



Regulation EC Nr. 1907/2006 Art.31

September 14th 2017

Date:

Product name: EM-Tec AG31 Silver filled epoxy, part A

Document Nr.: SDS00115002431A-02 **Version:** 2.0

6.3 Methods and material for containment and clean up

Clean up spills immediately

Collect spillage and wipe residue with a paper towel wetted with alcohol.

Collect spillage and dirty towels in a sealable waste container

Wash spill area with soap and water to remove last traces of residue

6.4 Reference to other sections

For further information see section 8

Section 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fumes/mist/vapours

Ensure adequate ventilation

Avoid contact with skin and eyes

Wash thoroughly after use

Wear protective gloves/protective clothing/eye protection

7.2 Conditions for safe storage, including any incompatibilities

Store locked up in a cool dry place Keep out of reach of children

7.3 Specific end uses(s)

Silver filled electrically conductive epoxy resin for use with hardener. Making electrically conductive bonds.

Section 8: Exposure control and personal protection

8.1. Control parameters

Exposure limits

Occupational exposure limits (OEL)



Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS00115002431A-02 **Version:** 2.0

Ingredient	TWA	STEL	Peak	Notes
Silver flakes (<1mm) - Ag	0.1mg/m3	Not available	Not available	Not available
4,4'-methylenebis [N,N-bis(2-oxiranylmethyl) aniline]	Not available	Not available	Not available	Not available
EM-Tec AG31 Silver filled epoxy, part A	Not available	Not available	Not available	Not available

8.2 Exposure controls

Control procedures: Ensure adequate ventilation

Personal protection: Take precautions to avoid contact with eyes and skin when handling the products

Inhalation: In case of insufficient ventilation, wear suitable respiratory equipment:

Air purifying respirator with organic gas/vapour cartridge (type A)

Hands and skin: Wear suitable gloves against chemicals; recommended gloves:

Nitrile

Eyes: Wear safety goggles or full-face protection

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance/physical state: Solid, paste
Colour: Silver grey
Odour: Not available
pH Not available
Boiling point/range: Not available
Flash point: >150°C (closed cup)

Evaporation rate: Not available **Explosion limits: upper limit:** Not available

lower limit: Not available

Vapour pressure: Not available **Specific gravity:** 2.5 g/cm3 @ 20°C

Solubility in water: Insoluble
Auto-ignition: Not available
Viscosity @40°C: >>20.5 mm²/s

9.2 Other information

VOC: Not available

Section 10: Stability and reactivity



Wateringweg 79 T
2031EK Haarlem E
The Netherlands I

T +31-85-2013155 E info@microtonano.com

Regulation EC Nr. 1907/2006 Art.31

September 14th 2017

Date:

Product name: EM-Tec AG31 Silver filled epoxy, part A

Version: 2.0

Document Nr.: SDS00115002431A-02

10.1. Reactivity

Reacts with amines

10.2 Chemical stability

Stable at normal temperatures and pressures

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purposes

10.4 Conditions to avoid

Incompatible substances

10.5 Incompatible materials

Strong oxidising agents, strong acids, strong bases, acetylene, ammonia, strong hydrogen peroxides

10.6 Hazardous decomposition products

Carbon oxides (CO, CO2), irritating smoke and toxic fumes

Section 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure:

Inhalation: May cause cough, irritation of the respiratory tract, sore throat, or asthma

Ingestion: May cause irritation

Skin contact: May cause mild skin irritation, redness, or rash

Eye contact: May cause redness, mild eye irritation

Chronic: Prolonged and repeated exposure may lead to skin sensitisation

Prolonged and repeated ingestion or inhalation of silver may yield to an irreversible

blue-grey discoloration of the skin

Toxicological data:

Ingredient	Toxicity	Irritation
------------	----------	------------



Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS00115002431A-02 **Version:** 2.0

Silver, metal	Dermal (rabbit) LD50: 2000mg/kg	Not established
	Inhalation (rat) LC50: 5.16mg/L (4h)	Not established
	Oral (Guinea pig) LD50: >5g/kg	Not established
4,4'-methylenebis [N,N-bis(2-oxiranylmethyl) aniline]	Dermal (rabbit) LD50: 3000g/kg	Not established
	Inhalation (rat) LC50: 24g/m3 (4h)	Not established
	Oral (rat) LD50: 5g/kg	Not established
EM-Tec AG32 Silver filled epoxy, part A	Not established	Not established

Section 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life

12.2 Persistence and degradability

The content is not readily biodegradable

12.3 Bioaccumulative potential

No information available

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available

12.6 Hazardous decomposition products

No experimental data available

Section 13: Disposal considerations

13.1. Waste treatment methods



Regulation EC Nr. 1907/2006 Art.31

September 14th 2017

Product name: EM-Tec AG31 Silver filled epoxy, part A

Document Nr.: SDS00115002431A-02

Version: 2.0

Date:

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised waste

collection point.

National regulations: Disposal should be in accordance with local, state or national legislation.

Section 14: Transport information

Labels required:



14.1. UN number

UN-number: 3077

14.2 UN proper shipping name

Proper shipping name: Environmentally hazardous substance, solid, N.O.S.

14.3 Transport hazard class(es)

Class: 9
ADR/RID-Classification code: E1

14.4 Packing group

Packing:IIILimited Quantity:5kgExcepted Quantity:30g

14.5 Incompatable materials

ADR/RID- Environmentally hazardous: Not applicable

IMDG-Marine pollutant: Yes

IATA/ICAO-Environmentally hazardous:Not applicable

14.6 Special precautions for user

Not applicable



Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS00115002431A-02 **Version:** 2.0

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

Not applicable

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UN-number: 3077

15.2 Chemical safety assessment

All substances are listed

Section 16: Other information

RoHS Directive Compliant

This product is fully compliant with the directive 2100/65/EU Annex II (RoHS). It does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's or PBDE's.

WEEE

This product is not a piece of electrical or electronic equipment, and it therefore not governed by Directive 2002/96/EC on waste electrical and electronic equipment (WEEE)

Abbreviations:

Carc. Carcinogenicity
Exp. Exposure
Flam. Flammable

GHS Global Harmonised System of Classification of Labelling Chemicals

Irrit. Irritant

LC50 Lethal Concentration 50%

LCLo Lowest published lethal concentration

LD50 Lethal Dose 50% N/A Not applicable N/E Not estimated

PBT Persistent Bioaccumulative and Toxic

WEL Workplace Exposure Limit Repr. Reproductive toxicant

RoHS Restriction of Hazardous Substance

STEL Short-Term Exposure Limit
STOT Specific Target Organ Toxicity

TCLo Lowest published toxic concentration vPvB very Persistent and very Bioaccumulative



Wateringweg 79 2031EK Haarlem The Netherlands T +31-85-2013155 E info@microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS00115002431A-02 **Version:** 2.0

WEEE Waste Electrical and Electronic Equipment

DSD / DPD label elements



Full

Text Risk and Hazard codes

H317: May cause an allergic skin reaction

H341: Suspected of causing genetic defects

H411: Toxic to aquatic life with long lasting effects

R38: Irritating to skin

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Safety advice:

S02 - Keep out of reach of children.

S09 – Keep container in a well-ventilated place.

S13 – Keep away from food, drink and animal feeding stuff.

S23 - Do not breath gas/fumes/vapour/spray.

S26 – In case of contact with eyes, rinse with plenty of water and seek medical help.

S281 – After contact with skin, wash immediately with detergent and plenty of waterways.

S29 – Do not empty in drains.

S35 – This material and its container must be disposed of in a safe way.

S36 – Wear suitable protective clothing.

S37 – Wear suitable gloves.

S38 – In case of insufficient ventilation, wear suitable respiratory equipment.

S39 - Wear eye / face protection.

S40 – In case of insufficient ventilation, wear suitable respiratory equipment.

S43 - In case of fire use....

S45 – In case of accident or if you feel unwell, immediately contact Doctor or Poisons information center (show label if possible).

S46 – If swallowed, seek immediate medical advice and show label if possible.

S52 – Not recommended for interior use on large surfaces.

S53 – Avoid exposure – obtain special instructions before use.

S56 – Dispose of this material and its container at hazardous or special waste collection point.

S57 – Use appropriate container to avoid environment contamination.

S61 - Avoid release to the environment

S63 – In case of accident by inhalation, remove casualty to fresh air and keep at rest.

S64 – If swallowed, rinse mouth with water (only if person is conscious)



Regulation EC Nr. 1907/2006 Art.31

Document Nr.: SDS00115002431A-02 **Version:** 2.0

This product should be stored, handled, and used in accordance with good industrial hygiene practices and in accordance with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe the product from the point of view of safety requirements. It does not guarantee any specific properties.

It is the responsibility of the user to query and verify any information seeming suspect or where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, state, federal and international regulations.



Regulation EC Nr. 1907/2006 Art.31

July 12th 2016

Date:

Product name: EM-Tec AG31 Silver filled epoxy, part B

Document Nr.: SDS00115002431B-01 **Version:** 1.0

Section 1: Identification of the substance or mixture and the company

1.1. Product Identifier

EM-Tec AG31 fast cure, high conductivity silver filled epoxy

1.2 Relevant identified uses of the substance or mixture and uses advised against

Silver filled electrically conductive epoxy hardener for use with resin.

Making electrically conductive bonds. Uses advised against: Not available

1.3. Details of the supplier of the Safety Data Sheet

Vof Micro to Nano Wateringweg 79 2031EK Haarlem Netherlands

Tel: +31(0)85-2013155 E: info@microtonano.com

1.4 Emergency telephone number

112 (NLD) or your national emergency telephone number for chemical spills, leaks, fires, exposures or accidents

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Physical: Low flammability

Health: Corrosive to eyes category 1

Skin corrosion/irritation category 1 Reproductive toxicity category 2 Chronic aquatic hazard category 1

Environment: Chronic aquatic hazard category Acute aquatic hazard category 1

Other hazards: None

Classification according to Regulation EC Nr. 1272/2008

Xi: Irritant Xn: Harmful C: Corrosive

Health: R38: Irritating to skin



Wateringweg 79
2031EK Haarlem
The Netherlands

T +31-85-2013155 E info@microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Date: Product name: EM-Tec AG31 Silver filled epoxy, part B July 12th 2016

Document Nr.: SDS00115002431B-01 Version: 1.0

R41: Risk of serious damage to eyes

R61: May cause harm to the unborn child

Physical Not classified

Environment: R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment

Other hazards: Not classified

2.2 Labeling elements

Labelling accordance to Regulation EC Nr. 1272/2008

Hazard pictogramm(s):

Signal word:

Hazard statement(s):

Causes severe skin burns and eye

cause an allergic skin reaction







Danger

H314:

damage

H317: May

H361: Suspected of damaging fertility or the unborn child H410: Very toxic to aquatic life with long lasting effects

Precautionary statement(s)

Prevention:

P102: Keep out of reach of children

P201+P202: Obtain special instructions before use. Do not handle until safety precautions have read and understood

P260: Do not breath fumes/vapours

P270: Do not eat, drink or smoke when using this product

P 272: Contaminated work clothing should not be allowed out of the

workplace

P 273: Avoid release to the environment

P280: Wear protective gloves/protective clothing/eye protection/face protection

Response:

P305+P351+P338: If in eyes: Rinse cautiously with water for several minutes

Remove contact lenses, if present and easy to do so. Continue

rinsing

P301+P330+P331: If swallowed: Rinse mount. Do not induce vomiting

P303+P361+P353: If on skin (or hair): Take off immediately all contimated clothing.

Rinse skin with water/shower.

P333+P313: If skin irritation or a rash occurs: Get medical attention

P304+P340: If inhaled: Remove person to fresh air and keep comfortable for

P363: Wash contaminated clothing before reuse



Wateringweg 79 2031EK Haarlem The Netherlands

T +31-85-2013155 E info@microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B Date: July 12th 2016

Document Nr.: SDS00115002431B-01 **Version:** 1.0

P308+P313: For all routed of exposure: If exposed or concerned: Get medical

attention

P391: Collect spillage

Storage: P405: Store locked up

Disposal: P501: Dispose of contents/container in accordance to local/regional/

international regulations

Supplemental hazard info: none

2.3 Other hazards

Argyria warning: Long term ingestion or inhalation of silver dust can lead to an irreversible

blue-grey discoloration of the skin

Section 3: Composition / information on components

3.1. Substances

Not applicable

3.2 Mixtures

Component	CAS Nr.	WT%
Silver flakes (<1mm) - Ag	7440-22-4	67
4-nonyl phenol, branched	84852-15-3	22
1-piperazineethanamine	140-31-8	7
Diethylene triamine, reaction product with diglycidyl ether of Bisphenol A	68411-71-2	1
Diethylene triamine	111-40-0	1
4,4'-isopropylidenediphenol	80-05-7	1

(* Explanation notes: see section 16)

Section 4: First aid measures

4.1. Description of first aid measures

Contact with eyes: Rinse cautiously with water for several minutes. If possible, remove contact

lenses. Continue rinsing.

Seek medical attention if irritation persists.

Contact with skin: Wash with water and soap.



Wateringweg 79 T +31-85-2013155
2031EK Haarlem E info@microtonano.com
The Netherlands I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B Date: July 12th 2016

Document Nr.: SDS00115002431B-01 **Version:** 1.0

Seek medical attention if irritation persists.

Inhalation: Fresh air, keep warm and at rest.

Seek medical attention of ill effects occur

Ingestion: If swallowed, do not induce vomiting

Seek immediate medical advice

If vomiting appears imminent or occurs hold patient's head down, lower than their

hips to help avoid possible aspiration of vomitus. Never give liquid to a person with reduced awareness

Give water to rinse out mouth, then provide water slowly as much as casually can

comfortably drink Avoid giving milk or oils Avoid giving alcohol

4.2. Important symptoms and effects, either immediate or delayed

Eye contact: Corrosive to eyes

Symptoms: redness, severe irritation, pain, burns

Immediately call a poison center/doctor

Skin contact: Corrosive to skin

Symptoms: redness, severe irritation, rash (allergic contact dermatitis), pains,

burns, blistering

Immediately call a poison center/doctor

Inhalation: Corrosive to the respiratory tract

Cough, severe irritation or burns

Immediately call a poison center/doctor

Ingestion: Corrosive to digestive tract

Symptoms: severe irritation, burns to mount, throat, stomach

Immediately call a poison center/doctor

4.3. Indication of any immediate medical attention and special treatment

General advise: If you feel unwell, seek medical advice; show product label if possible

If symptoms persist, always call a doctor

Section 5: Firefighting Measures 5.1. Extinguishing media

5.2 Special hazards arising from the substance or mixture

Use dry chemical, CO2, chemical foam or water spray. Use water spray to cool containers.

Not flammable or combustible, but will burn if involved in a fire. Produces carbon oxides (CO, CO2), irritating smoke and toxic fumes in fires



Wateringweg 79 2031EK Haarlem The Netherlands T +31-85-2013155
E info@microtonano.com
I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

July 12th 2016

Product name: EM-Tec AG31 Silver filled epoxy, part B **Date:**

Document Nr.: SDS00115002431B-01 **Version:** 1.0

Inhalation of toxic smoke or fumes may have delayed effects. Exposed person may need to be put under

surveillance for 4-12 hrs.

5.3 Advice to firefighters

Fight fire from a safe distance, with adequate cover Wear self-contained breathing apparatus and full fire fighting turn-out gear

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from extreme heat or open flames

Wear suitable protective clothing including eye/face protection

6.2 Environmental precautions

Avoid release to the environment

Do not allow to enter public sewers and waterways

6.3 Methods and material for containment and clean up

Clean up spills immediately

Collect spillage and wipe residue with a paper towel wetted with alcohol.

Collect spillage and dirty towels in a sealable waste container made of plastic or steel

Avoid containers with copper, aluminium, zinc or galvanised surfaces since the waste material can slowly oxidises these

Wash spill area with soap and water to remove last traces of residue

6.4 Reference to other sections

For further information see section 8

Section 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fumes/mist/vapours
Ensure adequate ventilation
Avoid contact with skin and eyes
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B Date: July 12th 2016

Document Nr.: SDS00115002431B-01 **Version:** 1.0

7.2 Conditions for safe storage, including any incompatibilities

Store locked up in a cool dry place Keep out of reach of children

7.3 Specific end uses(s)

Silver filled electrically conductive epoxy hardener for use with resin. Making electrically conductive bonds.

Section 8: Exposure control and personal protection

8.1. Control parameters

Exposure limits

Occupational exposure limits (OEL)

Ingedrient	TWA	STEL	Peak	Notes
Silver flakes (<1mm) - Ag	0.1mg/m3	Not available	Not available	Not available
Diethylene triamine	1 ppm	Not available	Not available	Not available
EM-Tec AG31 Silver filled epoxy, part B	Not available	Not available	Not available	Not available

8.2 Exposure controls

Control procedures: Ensure adequate ventilation

Personal protection: Take precautions to avoid contact with eyes and skin when handling the products

Inhalation: In case of insufficient ventilation, wear suitable respiratory equipment:

Air purifying respirator with organic gas/vapour cartridge (type A)

Hands and skin: Wear suitable gloves against chemicals; recommended gloves: Nitrile

Eyes: Wear safety goggles or full face protection

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance/physical state: Solid, paste
Colour: Silver grey
Odour: Amine-like
pH Not available
Boiling point/range: Noy available



Wateringweg 79 T +31-85-2013155
2031EK Haarlem E info@microtonano.com
The Netherlands I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

July 12th 2016

Product name: EM-Tec AG31 Silver filled epoxy, part B

Document Nr.: SDS00115002431B-01

Version: 1.0

Date:

Flash point: >93°C (closed cup)
Evaporation rate: Not available
Explosion limits: upper limit: Not available

lower limit: Not available

Vapour pressure: Not available **Specific gravity:** 2.4 g/cm3 @ 25°C

Solubility in water: Insoluble
Auto-ignition: Not available
Viscosity @40°C: >>20.5 mm²/s

9.2 Other information

VOC: Not available

Section 10: Stability and reactivity

10.1. Reactivity

Reacts exothermically with epoxide groups. May slowly attack metals such as aluminium, zinc, copper and their alloys.

10.2 Chemical stability

Stable at normal temperatures and pressures

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purposes

10.4 Conditions to avoid

Avoid excessive heat and incompatible substances

10.5 Incompatible materials

Strong oxidising agents, strong acids, strong bases, ammonia

10.6 Hazardous decomposition products

Carbon oxides (CO, CO2), ammonia, nitric aces, nitrogen oxides (NOx) and silver metal fumes

Section 11: Toxicological information

11.1. Information on toxicological effects



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B Date: July 12th 2016

Document Nr.: SDS00115002431B-01 **Version:** 1.0

Information on likely routes of exposure:

Eye contact: May cause redness, severe eye irritation, pain or corrosive eye damage

Skin contact: May cause serious skin irritation, redness, allergic contact dermititis and chemical burns

Inhalation: May cause cough and severe irritation of the respiratory tractIngestion: May cause severe irritations or burns to mouth, throat and stomach

Chronic: Prolonged and repeated exposure may lead to skin sensitisation and to reproductive

toxicity

Prolonged and repeated ingestion or inhalation of silver may yield to an irreversible

blue-grey discoloration of the skin

Toxicological data:

Ingredient	Toxicity	Irritation
Silver, metal	Dermal (rabbit) LD50: 2000mg/kg	Not established
	Inhalation (rat) LC50: 5.16mg/L (4h)	Not established
	Oral (Guinea pig) LD50: >5g/kg	Not established
4-nonyl phenol, branched	Dermal (rabbit) LD50: >3160mg/kg	Not established
	Inhalation (rat) LC50: Not established	Not established
	Oral (rat) LD50: 1300mg/kg	Not established
1-piperazineethanamine	Dermal (rabbit) LD50: 866mg/kg	Not established
	Inhalation (rat) LC50: Not established	Not established
	Oral (rat) LD50: 2140µL/kg	Not established
Diethylene triamine, reaction product with diglycidyl ether of Bisphenol A	Dermal (rabbit) LD50: Not established	Not established
	Inhalation (rat) LC50: Not established	Not established
Displicitor A	Oral (rat) LD50: Not established	Not established
Diethylene triamine	Dermal (rabbit) LD50: 1090mg/kg	Not established
	Inhalation (rat) LC50: Not established	Not established
	Oral (rat) LD50: 1800 mg/kg	Not established
4,4'-isopropylidenediphenol	Dermal (rabbit) LD50: 3mL/kg	Not established
	Inhalation (rat) LC50: >170mg/M3	Not established
	Oral (rat) LD50: 2400 mg/kg	Not established
EM-Tec AG31 Silver filled epoxy, part B	Not established	Not established



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B

Date: July 12th 2016

Document Nr.: SDS00115002431B-01

Version: 1.0

Section 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life

12.2 Persistence and degradability

The content is not readily biodegradable

12.3 Bioaccumulative potential

No information available

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available

12.6 Hazardous decomposition products

No experimental data available

Section 13: Disposal considerations

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way.

Do not discharge into drains or the environment, dispose to an authorised waste

collection point.

National regulations: Disposal should be in accordance with local, state or national legislation.

Section 14: Transport information Labels required:



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B

Document Nr.: SDS00115002431B-01

Date: July 12th 2016

Version: 1.0



14.1. UN number

UN-number: 3263

14.2 UN proper shipping name

Proper shipping name: Coorosive solid, basic, organic, N.O.S.

14.3 Transport hazard class(es)

Class: 8
ADR/RID-Classification code: E2

14.4 Packing group

Packing: II
Limited Quantity: 5kg
Excepted Quantity: 30g

14.5 Incompatable materials

ADR/RID- Environmentally hazardous: Not applicable

IMDG-Marine poluttant: Yes

IATA/ICAO-Environmentally hazardous:Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

Not applicable



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B Date: July 12th 2016

Document Nr.: SDS00115002431B-01 **Version:** 1.0

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UN-number: 3077

15.2 Chemical safety assessment

All substances are listed

Section 16: Other information

RoHS Directive Compliant

This product is fully compliant with the directive 2100/65/EU Annex II (RoHS). It does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's or PBDE's.

WEEE

This product is not a piece of electrical or electronic equipment, and it therefore not governed by Directive 2002/96/EC on waste electrical and electronic equipment (WEEE)

Abbreviations:

Asp. Tox Aspiration hazard Carc. Carcinogenicity Exp. Exposure Flam. Flammable

GHS Global Harmonised System of Classification of Labelling Chemicals

Irrit. Irritant

LC50 Lethal Concentration 50%

LCLo Lowest published lethal concentration

LD50 Lethal Dose 50% N/A Not applicable N/E Not estimated

PBT Persistent Bioaccumulative and Toxic

WEL Workplace Exposure Limit Repr. Reproductive toxitant

ROHS Restriction of Hazardous Substance
SEM Scanning Electron Microscope
STEL Short-Term Exposure Limit
STOT Specific Target Organ Toxicity

TCLo Lowest published toxic concentration vPvB very Persistent and very Bioaccumulative WEEE Waste Electrical and Electronic Equipment



Wateringweg 79 2031EK Haarlem The Netherlands T +31-85-2013155 E info@microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B Date: July 12th 2016

Document Nr.: SDS00115002431B-01 **Version:** 1.0

DSD / DPD label elements





Full Text Risk and Hazard codes

H314: Causes severe skin burns and eye damage

H317: May cause an allergic skin reaction

H361: Suspected of damaging fertility or the unborn child

H410: Very toxic to aquatic life with long lasting effects

R41: Risk of serious damage to eyes

R61: May cause harm to the unborn child

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Safety advice:

S02 - Keep out of reach of children.

S09 – Keep container in a well ventilated place.

S13 – Keep away from food, drink and animal feeding stuff.

S23 – Do not breath gas/fumes/vapour/spray.

S26 – In case of contact with eyes, rinse with plenty of water and seek medical help.

S281 – After contact with skin, wash immediately with detergent and plenty of waterways.

S29 – Do not empty in drains.

S35 – This materials and its container must be disposed of in a safe way.

S36 – Wear suitable protective clothing.

S37 – Wear suitable gloves.

S38 – In case of insufficient ventilation, wear suitable respiratory equipment.

S39 - Wear eye / face protection.

S40 – In case of insufficient ventilation, wear suitable respiratory equipment.

S43 – In case of fire use....

S45 – In case of accident or if you feel unwell, immediately contact Doctor or Poisons information center (show label if possible).

S46 – If swallowed, seek immediate medical advice and show label if possible.

S52 – Not recommended for interior use on large surfaces.

S53 – Avoid exposure – obtain special instructions before use.

S56 – Dispose of this materials and its container at hazardous or special waste collection point.

S57 – Use appropriate container to avoid environment contamination.

S61 - Avoid release to the environment

S63 – In case of accident by inhalation, remove casualty to fresh air and keep at rest.

S64 – If swallowed, rinse mouth with water (only if person is conscious)



Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG31 Silver filled epoxy, part B Date: July 12th 2016

Document Nr.: SDS00115002431B-01 **Version:** 1.0

This product should be stored, handled and used in accordance with good industrial hygiene practices and in accordance with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe the product from the point of view of safety requirements. It does not guarantee any specific properties.

It is the responsibility of the user to query and verify any information seeming suspect or where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, state, federal and international regulations.

