

Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

Section 1: Identification of the substance or mixture and the company

1.1. Product Identifier

EM-Tec AG30 long pot file, extreme conductivity silver filled epoxy

1.2 Relevant identified uses of the substance or mixture and uses advised against

Silver filled electrically conductive epoxy resin for use with hardener.
Making electrically conductive bonds.
Uses advised against: Not available

1.3. Details of the supplier of the Safety Data Sheet

Vof Micro to Nano
Tappersweg 91
2031ET Haarlem
Netherlands
Tel: +31(0)85-2013155
E: info@microtonano.com

1.4 Emergency telephone number

112 (NLD) or your national emergency telephone number for chemical spills, leaks, fires, exposures or accidents

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Physical:	Low flammability
Health:	Skin corrosion/irritation category 2
Environment:	Chronic aquatic hazard category 1 Acute aquatic hazard category 1
Other hazards:	None

Classification according to Regulation EC Nr. 1272/2008

	Xi: Irritant
	Xn: Harmful
Health:	R38: Irritating to skin
Physical	Not classified
Environment:	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

Other hazards: the aquatic environment
Not classified

2.2 Labeling elements

Labelling accordance to Regulation EC Nr. 1272/2008

Hazard pictogramm(s):



Signal word:

Warning

Hazard statement(s):

H317: May cause an allergic skin reaction
H341: Suspected of causing genetic defects
H410: Very toxic to aquatic life with long lasting effects

Precautionary statement(s)

Prevention:

P102: Keep out of reach of children
P201+P202: Obtain special instructions before use. Do not handle until safety precautions have read and understood
P261: Avoid breathing fumes/vapours/mist
P270: Do not eat, drink or smoke when using this product
P 272: Contaminated work clothing should not be allowed out of the workplace
P 273: Avoid release to the environment
P280: Wear protective gloves/protective clothing/eye protection/face protection

Response:

P308+P313: If exposed or concerned: Get medical attention
P302+P352: If on skin: Wash with plenty of water and soap.
P333+P313: If skin irritation or a rash occurs: Get medical attention
P362+P364: Take of contaminated clothing and wash before reuse

P391: Collect spillage

Storage:

P405: Store locked up

Disposal:

P501: Dispose of contents/container in accordance to local/regional/international regulations

Supplemental hazard info:

none

2.3 Other hazards

Argyria warning:

Long term ingestion or inhalation of silver dust can lead to an irreversible blue-grey discoloration of the skin

Dermatitis or Eczema's:

Prolonged and repeated exposure to uncured epoxy resins may cause dermatitis or eczema's



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

Section 3: Composition / information on components

3.1. Substances

Not applicable

3.2 Mixtures

Component	CAS Nr.	WT%
Silver flakes (<1mm) - Ag	7440-22-4	60-90
4,4'-methylene bis [N,N-bis(2-oxiranylmethyl) aniline]	28768-32-3	10-30
Neopentyl glycol diglycidyl ether	17557-23-2	1-5

(* Explanation notes: see section 16)

Section 4: First aid measures

4.1. Description of first aid measures

- Contact with eyes:** Rinse cautiously with water for several minutes. If possible, remove contact lenses. Continue rinsing.
Seek medical attention if irritation persists.
- Contact with skin:** Wash with water and soap.
Seek medical attention if irritation persists.
- Inhalation:** Fresh air, keep warm and at rest.
Seek medical attention if ill effects occur
- Ingestion:** If swallowed, do not induce vomiting
Seek immediate medical advice
If vomiting appears imminent or occurs hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.
Never give liquid to a person with reduced awareness
Give water to rinse out mouth, then provide water slowly as much as casually can comfortably drink
Avoid giving milk or oils
Avoid giving alcohol

4.2. Important symptoms and effects, either immediate or delayed

- Inhalation:** May cause irritation of the respiratory tract
Symptoms: cough, sore throat, asthma



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

Ingestion:	May cause digestive tract irritation Symptoms: sore throat, abdominal pain, nausea, vomiting
Skin contact:	Mildly irritating to skin Symptoms: redness and pain
Eye contact:	Irritating to eyes Symptoms: redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment

General advise: If you feel unwell, seek medical advice; show product label if possible
If symptoms persist, always call a doctor

Section 5: Firefighting Measures

5.1. Extinguishing media

Use dry chemical, CO₂, chemical foam or water spray. Use water spray to cool containers.

5.2 Special hazards arising from the substance or mixture

Not flammable or combustible, but will burn if involved in a fire.
Produces carbon oxides (CO, CO₂), irritating smoke and toxic fumes in fires

5.3 Advice to firefighters

Fight fire from a safe distance, with adequate cover
Wear self-contained breathing apparatus and full fire fighting turn-out gear

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Wear suitable protective clothing including eye/face protection

6.2 Environmental precautions

Avoid release to the environment
Do not allow to enter public sewers and waterways



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

6.3 Methods and material for containment and clean up

Clean up spills immediately
Collect spillage and wipe residue with a paper towel wetted with alcohol.
Collect spillage and dirty towels in a sealable waste container
Wash spill area with soap and water to remove last traces of residue

6.4 Reference to other sections

For further information see section 8

Section 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fumes/mist/vapours
Ensure adequate ventilation
Avoid contact with skin and eyes
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection

7.2 Conditions for safe storage, including any incompatibilities

Store locked up in a cool dry place
Keep out of reach of children

7.3 Specific end uses(s)

Silver filled electrically conductive epoxy resin for use with hardener.
Making electrically conductive bonds.

Section 8: Exposure control and personal protection

8.1. Control parameters

Exposure limits

Occupational exposure limits (OEL)

Ingedrient	TWA	STEL	Peak	Notes
Silver flakes (<1mm) - Ag	0.1mg/m3	Not available	Not available	Not available



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

4,4'-methylenebis [N,N-bis(2-oxiranylmethyl) aniline]	Not available	Not available	Not available	Not available
Neopentyl glycol diglycidyl ether	Not available	Not available	Not available	Not available
EM-Tec AG30 Silver filled epoxy, part A	Not available	Not available	Not available	Not available

8.2 Exposure controls

Control procedures: Ensure adequate ventilation
Personal protection: Take precautions to avoid contact with eyes and skin when handling the products
Inhalation: In case of insufficient ventilation, wear suitable respiratory equipment:
Air purifying respirator with organic gas/vapour cartridge (type A)
Hands and skin: Wear suitable gloves against chemicals; recommended gloves:
Nitrile
Eyes: Wear safety goggles or full face protection

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance/physical state: Solid, paste
Colour: Silver grey
Odour: Not available
pH Not available
Boiling point/range: Not available
Flash point: $\geq 127^{\circ}\text{C}$ (closed cup)
Evaporation rate: Not available
Explosion limits: upper limit: Not available
lower limit: Not available
Vapour pressure: Not available
Specific gravity: 3.56 g/cm³ @ 20°C
Solubility in water: Insoluble
Auto-ignition: Not available
Viscosity @40°C : $\gg 20.5 \text{ mm}^2/\text{s}$

9.2 Other information

VOC: Not available



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

Section 10: Stability and reactivity

10.1. Reactivity

Reacts with amines

10.2 Chemical stability

Stable at normal temperatures and pressures

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purposes

10.4 Conditions to avoid

Incompatible substances

10.5 Incompatible materials

Strong oxidising agents, strong acids, strong bases, acetylene, ammonia, strong hydrogen peroxides

10.6 Hazardous decomposition products

Carbon oxides (CO, CO₂), irritating smoke and toxic fumes

Section 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure:

- Inhalation:** May cause cough, irritation of the respiratory tract, sore throat or asthma
Ingestion: May cause irritation
Skin contact: May cause mild skin irritation, redness or rash
Eye contact: May cause redness, mild eye irritation
Chronic: Prolonged and repeated exposure may lead to skin sensitisation
Prolonged and repeated ingestion or inhalation of silver may yield to an irreversible blue-grey discoloration of the skin



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

Toxicological data:

Ingredient	Toxicity	Irritation
Silver, metal	Dermal (rabbit) LD50: 2000mg/kg	Not established
	Inhalation (rat) LC50: 5.16mg/L (4h)	Not established
	Oral (Guinea pig) LD50: >5g/kg	Not established
4,4'-methylenebis [N,N-bis(2-oxiranylmethyl) aniline]	Dermal (rabbit) LD50: 3000g/kg	Not established
	Inhalation (rat) LC50: 24g/m3 (4h)	Not established
	Oral (rat) LD50: 5g/kg	Not established
Neopentyl glycol diglycidyl ether	Dermal (rabbit) LD50: 2150mg/kg	Not established
	Inhalation (rat) LC50: Not established	Not established
	Oral (rat) LD50: 2000 mg/kg	Not established
EM-Tec AG30 Silver filled epoxy, part A	Not established	Not established

Section 12: Ecological information**12.1. Toxicity**

Very toxic to aquatic life

12.2 Persistence and degradability

The content is not readily biodegradable

12.3 Bioaccumulative potential

No information available

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

12.6 Hazardous decomposition products

No experimental data available

Section 13: Disposal considerations

13.1. Waste treatment methods

Product: This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point.

National regulations: Disposal should be in accordance with local, state or national legislation.

Section 14: Transport information

Labels required:



14.1. UN number

UN-number: 3077

14.2 UN proper shipping name

Proper shipping name: Environmentally hazardous substance, solid, N.O.S.

14.3 Transport hazard class(es)

Class: 9
ADR/RID-Classification code: E1

14.4 Packing group

Packing: III
Limited Quantity: 5kg
Excepted Quantity: 30g

14.5 Incompatible materials

ADR/RID- Environmentally hazardous: Not applicable



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

IMDG-Marine pollutant: Yes
IATA/ICAO-Environmentally hazardous: Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

Not applicable

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UN-number: 3077

15.2 Chemical safety assessment

All substances are listed

Section 16: Other information

RoHS Directive Compliant

This product is fully compliant with the directive 2100/65/EU Annex II (RoHS). It does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's or PBDE's.

WEEE

This product is not a piece of electrical or electronic equipment, and it therefore not governed by Directive 2002/96/EC on waste electrical and electronic equipment (WEEE)

Abbreviations:

Asp. Tox	Aspiration hazard
Carc.	Carcinogenicity
Exp.	Exposure
Flam.	Flammable
GHS	Global Harmonised System of Classification of Labelling Chemicals
Irrit.	Irritant
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
N/A	Not applicable



Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

N/E	Not estimated
PBT	Persistent Bioaccumulative and Toxic
WEL	Workplace Exposure Limit
Repr.	Reproductive toxicant
RoHS	Restriction of Hazardous Substance
SEM	Scanning Electron Microscope
STEL	Short-Term Exposure Limit
STOT	Specific Target Organ Toxicity
TCLo	Lowest published toxic concentration
vPvB	very Persistent and very Bioaccumulative
WEEE	Waste Electrical and Electronic Equipment

DSD / DPD label elements



Full Text Risk and Hazard codes

H317: May cause an allergic skin reaction
H341: Suspected of causing genetic defects
H411: Toxic to aquatic life with long lasting effects

R38: Irritating to skin
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Safety advice:

S02 – Keep out of reach of children.
S09 – Keep container in a well ventilated place.
S13 – Keep away from food, drink and animal feeding stuff.
S23 – Do not breath gas/fumes/vapour/spray.
S26 – In case of contact with eyes, rinse with plenty of water and seek medical help.
S281 – After contact with skin, wash immediately with detergent and plenty of waterways.
S29 – Do not empty in drains.
S35 – This materials and its container must be disposed of in a safe way.
S36 – Wear suitable protective clothing.
S37 – Wear suitable gloves.
S38 – In case of insufficient ventilation, wear suitable respiratory equipment.
S39 - Wear eye / face protection.
S40 – In case of insufficient ventilation, wear suitable respiratory equipment.
S43 – In case of fire use....
S45 – In case of accident or if you feel unwell, immediately contact Doctor or Poisons information center (show label if possible).
S46 – If swallowed, seek immediate medical advice and show label if possible.
S52 – Not recommended for interior use on large surfaces.



Safety Data Sheet

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec AG30 Silver filled epoxy, part A
Document Nr.: SDS00115002430A-01

Date: February 2nd 2022
Version: 2.0

- S53 – Avoid exposure – obtain special instructions before use.
- S56 – Dispose of this materials and its container at hazardous or special waste collection point.
- S57 – Use appropriate container to avoid environment contamination.
- S61 – Avoid release to the environment
- S63 – In case of accident by inhalation, remove casualty to fresh air and keep at rest.
- S64 – If swallowed, rinse mouth with water (only if person is conscious)

This product should be stored, handled and used in accordance with good industrial hygiene practices and in accordance with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe the product from the point of view of safety requirements. It does not guarantee any specific properties.

It is the responsibility of the user to query and verify any information seeming suspect or where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, state, federal and international regulations.



Micro to Nano
Innovative Microscopy Supplies

Tappersweg 91
2031ET Haarlem
The Netherlands

T +31-85-2013155
E info@microtonano.com
I www.microtonano.com