Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01
 Date:
 October 5th 2022

 Version:
 4.0
 Page 1 of 12

Section 1: Identification of the substance or mixture and the company

1.1. Product Identifier

EM-Tec STC39 Acetone solvent / thinner / cleaner EC #: 200-662-2 CAS #: 67-64-1 Registration number (REACH): 01-2119471330-49-xxxx Index number in CLP Annex VI: 606-001-00-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Diluting, removing, and cleaning of EM-Tec acetone-based carbon/silver/nickel paint

1.3. Details of the supplier of the Safety Data Sheet

Vof Micro to Nano Tappersweg 91 2031ET Haarlem Netherlands Tel: +31(0)85-2013155 E: info@microtonano.com

1.4 Emergency telephone number

112 (NLD) or your national emergency telephone number for chemical spills, leaks, fires, exposures or accidents

Section 2: Hazards identification

2.1. Classification of the substance or mixture according to Regulation EC Nr. 1272/2008

Physical: Health:	Flammable liquid, category 2, H225 Serious eye damage, category 2, H319 Specific target organ toxicity – single exposure, category 3, H336 (narcotic effects, drowsiness)
Environment:	Not classified
Other hazards:	Not classified
Environment:	Not classified
Other hazards:	Repeated exposure may cause skin dryness or cracking

(Contd. on page 2)



Tappersweg 91 2031ET Haarlem The Netherlands

- E info@microtonano.com
- I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01
 Date:
 October 5th 2022

 Version:
 4.0
 Page 2 of 12

2.2 Labelling elements accordance to Regulation EC Nr. 1272/2008

Hazard pictogramm(s):



Signal word:	Danger
Hazard statement(s):	H225: Highly flammable liquid and vapour
	H319: Causes serious eye irritation
	H336: May cause drowsiness or dizziness
Precautionary statement(s):	P102: Keep out of reach of children
	P210: Keep away from heat, hot surfaces, sparks, open flames and other
	ignition sources. No smoking
	P233: Keep container tightly closed
	P241: Use explosion-proof (electrical/ventilating/lighting) equipment
	P280: Wear protective gloves/protective clothing/eye protection/face
	protection
P305+P353	1+P338: If in eyes: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do so. Continue rinsing
	P337/313: If eye irritation persists; get medical advice/attention
	P370/378: In case of fire: Use foam or dry agent for extinction
	P405: Store locked up
	P501-2: Dispose of contents/container to an authorised waste collection
	point

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, the substance is not a PBT or a vPvB

(Contd. on page 3)



Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155

E info@microtonano.com

I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01
 Date:
 October 5th 2022

 Version:
 4.0
 Page 3 of 12

(Contd. of page 2)

Section 3: Composition / information on components

3.1. Substances

1. CAS No 2. EC No 3. Index No 4. REACH No	% (weight)	Name	Classification according to regulation Nr 1272/2008 [CLP]
67-64-1 200-662-2 606-001-00-8 01-2119471330-49-xxxx	100	Acetone 2-Propanone	Flam. Liq. 2, Eye Irri. 2A, STOT SE 3; H225, H319, H335, EUH066

(* Explanation notes: see section 16)

3.2 Mixtures

Not applicable

Section 4: First aid measures

4.1. Description of first aid measures

General information:	The usual precautions for handling chemical substances should be observed. If symptoms should occur, seek medical advice. Immediately remove any clothing soiled by the product
Contact with eyes:	Rinse cautiously with water for several minutes. If possible, remove contact lenses. Continue rinsing.
Contact with skin:	Wash with water and soap. Seek medical attention if irritation persists.
Inhalation:	Fresh air, keep warm and at rest. Seek medical attention of ill effects occur
Ingestion:	If swallowed, do not induce vomiting Seek immediate medical advice

4.2. Important symptoms and effects, either immediate or delayed

Irritation, nausea, vomiting, headache, vertigo, dizziness, drowsiness, gastrointestinal complaints, narcosis

(Contd. on page 4)



Tappersweg 91 2031ET Haarlem The Netherlands

- E info@microtonano.com
- I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01
 Date:
 October 5th 2022

 Version:
 4.0
 Page 4 of 12

(Contd. of page 3)

4.3. Indication of any immediate medical attention and special treatment

No further relevant information available

Section 5: Firefighting Measures

5.1. Extinguishing media

Alcohol resistant foam. Water spray. Dry extinguishing powder. BC powder. Carbon dioxide. Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour/air mixture. Solvent vapours are heavier than air and may spread along floors and form explosive mixtures with air. Places which are not ventilated, e.g. unventilated ground level areas such as trenches, conduits and shafts are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

In case of fire: carbon monoxide (CO) and carbon dioxide (CO2) may be formed.

5.3 Advice to firefighters

Fight fire from a safe distance, with adequate cover Do not move the load if exposed to heat. In case of fire; do not breathe fumes Wear self-contained breathing apparatus for fire fighting

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources Ensure adequate ventilation Wear suitable protective clothing including eye/face protection

6.2 Environmental precautions

Avoid release to the environment Do not allow to enter public sewers and waterways

(Contd. page 5)



Tappersweg 91 2031ET Haarlem The Netherlands

- E info@microtonano.com
- I www.microtonano.com

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01

Regulation EC Nr. 1907/2006 Art.31

 Date:
 October 5th 2022

 Version:
 4.0
 Page 5 of 12

6.3 Methods and material for containment and clean up

Absorb spillage in suitable liquid binding inert material Clean up spills immediately Avoid breathing vapours Control personal contact with the substance, by using protective equipment Collect spillage, absorbed spillage and wipes in a flammable waste container Wash spill area with soap and water to remove last traces of residue

6.4 Reference to other sections

See Section 7 for information on safe handling See section 8 for information on personal protection equipment See section 13 for disposal information

Section 7: Handling and storage

7.1. Precautions for safe handling

Keep away from sources of ignition Take precautions against static discharges Equipment should be grounded Use explosion proof electrical/ventilating/lighting/equipment Only use non-sparking tools Do not breathe aerosols or vapours Ensure adequate ventilation Avoid contact with skin and eyes Wash thoroughly after use Wear protective gloves/protective clothing/eye protection/face protection Have eyewash bottles available

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place Keep away from ignition sources Store away from oxidising agents Keep out of reach of children

7.3 Specific end uses(s)

Solvent / thinner / cleaner for EM-Tec solvent based silver / nickel / carbon paint / cement /paste. (Contd. on page 6)



Tappersweg 91 2031ET Haarlem The Netherlands

T +31-85-2013155

- E info@microtonano.com
- I www.microtonano.com

(Contd. of page 4)

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01

Regulation EC Nr. 1907/2006 Art.31

 Date:
 October 5th 2022

 Version:
 4.0
 Page 6 of 12

(Contd. of page 5)

Section 8: Exposure control and personal protection

8.1. Control parameters

Exposure limits

Occupational exposure limits (OEL)

Ingredient	Material Name	Source	TWA	STEL	Ceiling - C	Notes
Acetone	Acetone	EU	500ppm	1210 mg/m3	Not available	2000/39/EC

8.2 Exposure controls

Control procedures:	Ensure adequate ventilation Keep away from heat sources and ignition sources Take precautions against static discharges
Personal protection:	Take precautions to avoid contact with eyes and skin when handling the products Ensure adequate ventilation
Inhalation:	In case of insufficient ventilation, wear suitable respiratory equipment:
Hands and skin:	Air purifying respirator with organic gas/vapour cartridge (type A) Wear suitable gloves against chemicals; recommended gloves: Nitrile
Eyes:	Wear safety goggles or full-face protection

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance/physical state: Colour:	Liquid colourless
Odour:	mild sweet – fruity
pH value:	5-6 (in aqueous solution)
Melting point :	-94.8°C
Boiling point/range:	56.05°C
Flash point:	-17°C (closed cup)
Relative evaporation rate:	6
Explosion limits: upper limit:	12.8%
lower limit:	2.6%
Vapour pressure:	240 hPa
Relative density:	0.79 g/cm3 @ 20°C
Solubility in water:	soluble



Micro to Nano

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands (Contd. on page 7)

- E info@microtonano.com
- I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01
 Date:
 October 5th 2022

 Version:
 4.0
 Page 7 of 12

(Contd. of page 6)

Auto-ignition: Viscosity: 465°C 0.32 mPa s @ 20°C

9.2 Other information

VOC:

100% Acetone

Section 10: Stability and reactivity

10.1. Reactivity

It is a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air

10.2 Chemical stability

Stable under normal conditions

10.3 Possibility of hazardous reactions

May react violently with oxidants. Exothermic reaction with alkali's halogenated hydrocarbons. Danger of explosion: Chloroform, Hydrogen peroxide

10.4 Conditions to avoid

Direct sunlight. High temperatures. Incompatible materials. Open flame. Sparks

10.5 Incompatible materials

Ammonia. Strong oxidisers. Strong acids

10.6 Hazardous decomposition products

CO, CO2.

(Contd. on page 8)



Tappersweg 91 2031ET Haarlem The Netherlands

- E info@microtonano.com
- I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01
 Date:
 October 5th 2022

 Version:
 4.0
 Page 8 of 12

(Contd. of page 7)

Section 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure:

Inhalation:	Inhalation of solvent vapours may give rise to nausea, headaches, and dizziness		
Skin contact:	•	contact will result in defatting of the skin, leading to irritation and in some	
	cases to derma	atitis	
Eye contact:	Causes serious	s eye irritation	
CMR effects:	Carcinogenicit	y classification criteria not met based on available data	
	Germ cell mutagenicity classification criteria not met based on available data		
	Reproductive toxicity classification criteria not met based on available data		
STOT-single exposure: may cause drowsiness or dizziness		may cause drowsiness or dizziness	
STOT- repeated exposure:		classification criteria not met based on available data	
Aspiration haz	Aspiration hazard: classification criteria not met based on available data		

Toxicological data:

Ingredient	Toxicity	Notes
Acetone	Oral (rat) LD50: 5045 mg/kg	

Symptoms related to physical, chemical and toxicological characteristics

ting, nausea, gastrointestinal complaints
es serious eye irritation, corneal opacity
nt effects, headache, vertigo, fatigue, dizziness, narcosis ated exposure may cause skin dryness or cracking

11.2. Endocrine disrupting properties

Not listed

11.3. Toxicity

There is no additional information

Section 12: Ecological information

12.1. Toxicity

Shall not be classified as hazardous to the aquatic environment



Tappersweg 91 2031ET Haarlem The Netherlands (Contd. on page 9)

T +31-85-2013155

E info@microtonano.com

I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01
 Date:
 October 5th 2022

 Version:
 4.0
 Page 9 of 12

(Contd. of page 8)

12.2 Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Acetone	Readily biodegradable	Medium

12.3 Bio-accumulative potential

Ingredient	Bioaccumulation
Acetone	LOW (Log Kow < 4)

12.4 Mobility in soil

Ingredient	Mobility
Acetone	HIGH

12.5 Results of PBT and vPvB assessment

No information available

12.6 Hazardous decomposition products

No experimental data available

Section 13: Disposal considerations

13.1. Waste treatment methods

Product:	This material and its container must be disposed of as hazardous.	
	Do not discharge into drains or the environment, dispose to an authorised waste	
	collection point.	
National regulations:	Disposal should be in accordance with local, state or national legislation.	

(Contd. on page 10)



Tappersweg 91 2031ET Haarlem The Netherlands

- E info@microtonano.com
- I www.microtonano.com

Safety Data Sheet		Regulation EC Nr. 1907/2006 Art.31	
vent / thinner / cleaner	Date: October Version: 4.0	5th 2022 Page 10 of 1 2	
		(Contd. of page 9	
1090			
1000			
Acatana			
Acetone			
3			
F1			
Ш			
1L			
ous: Not applicable			
No relevant data			
dous: No relevant data			
(D/E)			
F-E, S-D			
353			
	1090 Acetone 3 F1 II 1L II 1L Ous: Not applicable No relevant data dous: No relevant data dous: No relevant data	vent / thinner / cleaner Date: October Version: 4.0 1090 1090 Acetone 3 F1 II 1L ous: Not applicable No relevant data hous: No relevant data (D/E) F-E, S-D	

	1 2, 3
IATA/ICAO-PAX:	353
IATA/ICAO-CAO:	364
IATA/ICAO-DGR:	Y341



Tappersweg 91 2031ET Haarlem The Netherlands

T +31-85-2013155 E info@microtonano.com

I www.microtonano.com

(Contd. on page 11)

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01

Regulation EC Nr. 1907/2006 Art.31

Date: October 5th 2022 Version: 4.0 Page **11** of **12**

(Contd. of page 10)

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

Not applicable

Section 15: Regulatory information

15.1. Safety, health, and environmental regulations/legislation specific for the substance or mixture

UN-number:

1090

15.2 Chemical safety assessment

No information available

Section 16: Other information

RoHS Directive Compliant

This product is fully compliant with the directive 2100/65/EU Annex II (RoHS). It does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's or PBDE's.

WEEE

This product is not a piece of electrical or electronic equipment, and it therefore not governed by Directive 2002/96/EC on waste electrical and electronic equipment (WEEE)

Abbreviations:

Asp. Tox	Aspiration hazard	
Carc.	Carcinogenicity	
Exp.	Exposure	
Flam.	Flammable	
GHS	Global Harmonised System of Classification of Labelling	g Chemicals
Irrit.	Irritant	
LC50	Lethal Concentration 50%	
LCLo	Lowest published lethal concentration	
LD50	Lethal Dose 50%	
N/A	Not applicable	
N/E	Not estimated	
PBT	Persistent Bio-accumulative and Toxic	
WEL	Workplace Exposure Limit	
Repr.	Reproductive toxicant	
RoHS	Restriction of Hazardous Substance	
SEM	Scanning Electron Microscope	
STEL	Short-Term Exposure Limit	
STOT	Specific Target Organ Toxicity	(Contd. on page 1



Micro to Nano

Innovative Microscopy Supplies

Tappersweg 91 2031ET Haarlem The Netherlands 12)

- T +31-85-2013155
- E info@microtonano.com
- I www.microtonano.com

Regulation EC Nr. 1907/2006 Art.31

Product name: EM-Tec STC39 Acetone solvent / thinner / cleaner Document Nr.: SDS0015001160-01

Date:	October 5th 2	.022
Version:	4.0	Page 12 of 12

TCLo	Lowest published toxic concentration	(Contd. of page 11)
vPvB	very Persistent and very Bio-accumulative	
WEEE	Waste Electrical and Electronic Equipment	

DSD / DPD label elements



Relevant phrases

H225 – Highly flammable liquid and vapour.

H319 – Causes serious eye irritation.

H336 - May cause drowsiness or dizziness

This product should be stored, handled, and used in accordance with good industrial hygiene practices and in accordance with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe the product from the point of view of safety requirements. It does not guarantee any specific properties.

It is the responsibility of the user to query and verify any information seeming suspect or where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, state, federal and international regulations.

End of document



Tappersweg 91 2031ET Haarlem The Netherlands T +31-85-2013155

E info@microtonano.com

I www.microtonano.com